

RISMALUCE mix colori forti



Rismette di carte e cartoncini in colori assortiti per tutti i sistemi di copiatura e stampa (inkjet, laser, offset). Le carte sono ricavate da impasti a base di cellulose selezionate chlorine-free (ECF) non provenienti da foreste vergini.

Mixed-colour paper and cardboard reams suitable for all kind of photocopying and printing (inkjet, laser, offset). The paper is obtained from selected chlorine-free (ECF) cellulose, which does not derive from virgin forests.

A4 21x29,7 cm

90 g/m ²	140 g/m ²	200 g/m ²
300 fogli	200 fogli	125 fogli
8 colori	6 colori	8 colori
A66X314	A65X214	A67X114

A3 29,7x42 cm

90 g/m ²	140 g/m ²	200 g/m ²
300 fogli	200 fogli	125 fogli
8 colori	6 colori	8 colori
A66X313	A65X213	A67X113

Sottoimballo / Inner	Imballo / Outer
A4 -	10 pz/pcs
A3 -	5 pz/pcs

RISMACQUA mix colori tenui



Rismette di carte e cartoncini in colori assortiti per tutti i sistemi di copiatura e stampa (inkjet, laser, offset). Le carte sono ricavate da impasti a base di cellulose selezionate chlorine-free (ECF) non provenienti da foreste vergini.

Mixed-colour paper and cardboard reams suitable for all kind of photocopying and printing (inkjet, laser, offset). The paper is obtained from selected chlorine-free (ECF) cellulose, which does not derive from virgin forests.

A4 21x29,7 cm (5 colori)

90 g/m ²	140 g/m ²	200 g/m ²
300 fogli	200 fogli	125 fogli
A66X324	A65X224	A67X124

A3 29,7x42 cm (5 colori)

90 g/m ²	140 g/m ²	200 g/m ²
300 fogli	200 fogli	125 fogli
A66X323	A65X223	A67X123

Sottoimballo / Inner	Imballo / Outer
A4 -	10 pz/pcs
A3 -	5 pz/pcs

RISMALUCE / RISMACQUA SCHEDA TECNICA – TECHNICAL CHART

Characteristic	Standard	Unit	rismaluce / acqua 90 g.	rismaluce / acqua 140 g.	rismaluce / acqua 200 g.
Grammage / Gramatura	ISO 536	g/m ²	90±5%	140±5%	200±5%
Thickness / Spessore	ISO 534	µm	116±5%	172±5%	228±5%
Bulk / Mano	ISO 534	cm ³ /g	1,29	1,23	1,14
CIE dL*	ISO 2469-70	-	45-92	45-92	45-92
burst index	ISO 2758	kPa*m2/g	2,8	3,0	2,3
ash content/ceneri	ISO 1762	%	16-20	16-20	16-20
Roughness/Liscio Bendtsen FELT SID	ISO 8791-2	ml/min	200±50	200±50	200±50
Roughness/Liscio Bendtsen WIRE SID	ISO 8791-2	ml/min	200±50	200±50	200±50
Absolute Humidity	ISO 287	%	6.0±1.0	6.0±1.0	7.0±1.0

1. Paper type: MULTIPURPOSE PAPER / OFFICE PAPER
2. Degree of processing: UNCOATED PAPER
3. Specifications (A3 = cm 29,7x42 – A4 = cm 21x29,7)
4. Fiber type and composition: 25% LONG FIBERS; 75% SHORT FIBERS (BLEACHED CHEMICAL PULP)
5. Manufacturer name: CARTOTECNICA FAVINI S.R.L.
6. COLOURED PAPER

Data / Date: 3.08.2017

Cartotecnica Favini S.r.l.

Direttore Generale
Andrea Bertone

