

RISMALUCE



Sottoimballo / Inner

Imballo / Outer

A4 -

5 pz/pcs

A3 -

5 pz/pcs

Carte e cartoncini dai colori forti per l'ufficio, la casa, la scuola e il tempo libero. Ideali per tutti i sistemi di copiatura e stampa. Le carte sono ricavate da impasti a base di cellulose selezionate chlorine-free (ECF) non provenienti da foreste vergini. L'imballo del formato A4 è totalmente **plastic-free**.

*Multipurpose, bright coloured paper and cardboard for office, home, school uses and leisure. Ideal for all kind of photocopying and printing. The paper is obtained from selected chlorine-free (ECF) cellulose, which does not derive from virgin forests. A4 package is **plastic-free**.*

A4 21x29,7 cm

A3 29,7x42 cm

		90 g/m ² 300 fogli	140 g/m ² 200 fogli	200 g/m ² 125 fogli	90 g/m ² 300 fogli	140 g/m ² 200 fogli	200 g/m ² 125 fogli
	53 giallo sole	A66B304	A65B204	A67B104	A66B313	A65B213	A67B113
	52 giallo oro	A66H304	A65H204	A67H104	A66H313		
	56 arancio	A66E304	A65E204	A67E104	A66E313	A65E213	A67E113
	61 scarlatto	A66C304	A65C204	A67C104	A66C313	A65C213	A67C113
	58 ciclamino	A66F304	A65F204	A67F104	A66F313		
	55 azzurro	A66G304	A65G204	A67G104	A66G313	A65G213	A67G113
	60 verde	A66D304	A65D204	A67D104	A66D313	A65D213	A67D113
	54 pistacchio	A66M304	A65M204	A67M104	A66M313		A67M113
	78 deserto	A667304		A677104			
	75 marrone			A67N104			
	49 violetto	A66J304		A67J104			
	62 blu di prussia			A67K104			A67K113
	66 blu cobalto			A672114			
	63 nero	A66A304		A67A134	A66A313		A67A133
	72 grafite			A674104			
	14 pietra	A665314		A675114			

RISMALUCE / RISMACQUA SCHEDA TECNICA – TECHNICAL CHART

Characteristic	Standard	Unit	rismaluce / acqua 90 g.	rismaluce / acqua 140 g.	rismaluce / acqua 200 g.
Grammage / Grammaturo	ISO 536	g/m ²	90±5%	140±5%	200±5%
Thickness / Spessore	ISO 534	µm	116±5%	172±5%	228±5%
Bulk / Mano	ISO 534	cm ³ /g	1,29	1,23	1,14
CIE dL*	ISO 2469-70	-	45-92	45-92	45-92
burst index	ISO 2758	kPa*m2/g	2,8	3,0	2,3
ash content/ceneri	ISO 1762	%	16-20	16-20	16-20
Roughness/Liscio Bendtsen FELT SID	ISO 8791-2	ml/min	200±50	200±50	200±50
Roughness/Liscio Bendtsen WIRE SID	ISO 8791-2	ml/min	200±50	200±50	200±50
Absolute Humidity	ISO 287	%	6.0±1.0	6.0±1.0	7.0±1.0

1. Paper type: MULTIPURPOSE PAPER / OFFICE PAPER
2. Degree of processing: UNCOATED PAPER
3. Specifications (A3 = cm 29,7x42 – A4 = cm 21x29,7)
4. Fiber type and composition: 25% LONG FIBERS; 75% SHORT FIBERS (BLEACHED CHEMICAL PULP)
5. Manufacturer name: CARTOTECNICA FAVINI S.R.L.
6. COLOURED PAPER

Data / Date: 3.08.2017

Cartotecnica Favini S.r.l.

Direttore Generale
Andrea Bertone

