

Risparmia fino al 15%! Le etichette DYMO® multi-pack sono ideali per grandi volumi di etichettatura!

Etichette cartacee originali DYMO® LabelWriter: per stampare facilmente una o centinaia di etichette.

- ▶ Grazie alla tecnologia di stampa a trasferimento termico diretto sarà possibile stampare testi perfettamente leggibili senza spendere soldi per costosi inchiostri o toner
- ▶ Nessun inceppamento, nessun problema di layout, nessuno spreco
- ▶ Disponibili in diversi formati per corrispondenza, codici a barre, spedizioni e applicazioni speciali

Le etichette D1 Standard originali DYMO® offrono le prestazioni e la varietà necessarie per soddisfare qualsiasi esigenza di etichettatura.

- ▶ 'Grazie al pre-taglio sul retro è possibile un'applicazione rapida e senza problemi
- ▶ Così versatile da poter gestire un'ampia gamma di lavori di etichettatura sia a casa che in ufficio
- ▶ Aderiscono alla maggior parte delle superfici pulite e piate

Esempio	Digitare	Descrizione	SKU	EAN	Rotoli
	LW Address Labels	LW STD ADDRESS LABELS 28 x 89mm	2093091	3026980930912	12/130
		LW STANDARD ADDRESS LAB 28 x 89mm	S0722360	5411313131889	24/130
		LW LG ADDRESS LABELS 36 x 89mm	2093093	3026980930936	12/240
		LW LARGE ADDRESS LABELS 36 x 89mm	S0722390	5411313131872	24/260
	LW Shipping Labels	LW SHIPPING LABELS 54 x 101mm	2093092	3026980930929	6/220
		LW SHIPPER LABELS 54 x 101mm	S0722420	5411313131865	12/220
	LW Multipurpose Labels	LW MULTIPURPOSE LABELS 32 x 57mm	2093094	3026980930943	6/1000
		LW MULTIPURPOSE LABELS 32 x 57mm	2093095	3026980930950	12/1000
	D1 Plastic Labels	D1 BK/WHI 9mm X 7m	2093096	3026980930967	10
		D1 BK/WHI 12mm X 7m	2093097	3026980930974	10
		D1 BK/WHI 19mm X 7m	2093098	3026980930981	10





Technical Data Sheet
Final version ; edition 2
Date: 23/10/02

DYMO LabelWriter Removable

(1) Description

DYMO LabelWriter Removable product is a paper label with a removable adhesive. The product is supplied on a roll. The labels are printed on the LabelWriter with a thermo-direct printing process, which involves no messy ink ribbons, toner or cartridges. Individual labels or whole rolls can be printed with laser like print quality. The product is recommended for indoor use only. Direct and indirect exposure to sunlight as well as high temperatures and high humidity must be avoided.

Property	Unit	Value	Test method
1. General			
- Thickness tape	Micron	155 ± 10	Micrometer
- Thickness liner	Micron	55 ± 5	
2. Adhesive properties			
		Dwell¹	
		20 min 24 hrs	
- to stainless steel	N/25mm	3 4	PSTC-1
- to glass		3 4	
- to PVC		2 3	
- to textured ABS		2 3	
- to powder coated steel		1 3	
- to wood		1 2	
- to polypropylene film matt		1 2	
- to polypropylene film glossy		3 4	
- to polyethylene		3 4	
- to Lever Arch File		1 1	
- to steel computer casing		1 1	

¹ Dwell denotes the contact time between label and surface

3. Abrasion resistance² of text Printed in LabelWriter Turbo 330 - Pencil erasure - Polystyrene pin - Sandpaper	30x 30x 30x	No visible effect No visible effect No visible effect	Crockmeter, 900g weight/arm
4. Light stability of printed label³ - in sun tester with glass filter (corresponds with direct exposure behind 3 mm window glass)		Background yellows. Text fades but still legible.	
5. Temperature stability - Application temperature - Service temperature 30 days in consumer deep freezer 24h at 50°C 10 minutes at 85°C	°C	Room temperature -20 to 50 °C No visible effect No visible effect No changes in print quality. Background becomes grey.	
6. Humidity resistance of applied label - 30 days at 40°C, 95 % R.H. (on alu panel)		To be done	
7. Shelf life of label roll - 1 year at 5-25°C and 40-80% relative humidity in its original packaging		Avoid exposure to heat, humidity & sunlight	

² Abrasion resistance: The printed labels are subjected to different scratching sources for a fixed number of cycles with a finger weight of 900g.

³ Resistance up to wool scale 4. This corresponds with 24 summer days and 48 winter days exposure behind window glass.